

SPS-5 / SPS-9

The SPS series Fiber Splice Shelves provides complete fiber tube and single or mass fusion splice management. The SPS-5 will accept up to 6 splice trays; up to 144 single fusion / 432 mass. The SPS-9 will accept up to 12 splice trays; up to 288 single / 864 mass. SPS shelves are compatible with all TSL patch panel series and have been designed to meet Telcordia GR-63 and GR-449 Fiber Distribution Frame System requirements.



Applications

- Telecommunications closets
- Central offices
- Data centers
- Remote distribution terminals

Features

- Flexible rack & stack design
- Top and bottom cable pass through entry
- Accepts standard 7" and 8.75" splice trays
- 19 or 23 inch rackmount
- Cable entry strain relief kit

Specifications

Model	SPS-5	SPS-9
Part Number	RM3UWSS	RM5UWSS
Dimensions (HxWxD) [in]	5.25 x 17 x 11	8.75 x 17 x 11
Rack Units	3	5
Empty shipping weight [lbs]	10	15
Splice Tray compatible	7" & 8.75"	7" & 8.75"
Splice Tray capacity	6	12
Single Fusion Capacity	144	288
Mass Fusion Capacity	864	1728
Material	Aluminum	Aluminum
Finish	CO White	CO White

Accessories

Accessory Description	Part Number
7" Splice Tray 12 Single / 72 Mass fusion	TRAY7
8-3/4" Splice Tray 24 Single / 72 Mass fusion	TRAY8
Kit Cable Entry (additional)	KT-RM-ENTRY